

# PRESSURE GAUGE

**Sn<sup>o</sup>wate**

Hengshui Snowate Environmental  
Technology Co., Ltd.

2022

EDITION FOR  
SNOWATE CATALOG





# 1.5" 耐震压力表

## LIQUID FILLED PRESSURE GAUGE

型号 MODEL	规格 SPEC	测压范围 PRESSURE	接口尺寸 PORT	精度 PRECISION
YN 40	径向	0.16 0.4 0.6	ZG 1/8" ZG 1/4"	
YN 40Z	轴向	0.7 1 1.6	φ4	2.5
YN 40ZT	轴向带边	2.5 3 4	φ6	
YN 40ZK	轴向插管	6 10 -0.1(Mpa)	M10 × 1	



### 耐震压力表工作条件及 安装使用注意事项

- 环境温度须在 -40 ~ 70 摄氏度之间
- 相对湿度必须 ≤ 80%
- 工作震动频率 ≤ 25 hz 振幅, ≤ 1 mm 介质振动
- 工作压力静压测量压力在上限压力的 1/3 ~ 3/4, 波动压力条件下测量压力值应在上限的 1/3 ~ 2/3
- 仪表必须垂直安装
- 安装、拆卸时严禁用手扳外壳

### 国家计量器具制造许可证 及型式批准证书

菲利特研发生产的压力表等精密计量器具, 通过国家专业机构检测认证, 准许生产制造, 质量达到国家强制标准, 保证您的生产安全和精密监测需要。



## 压力表系列 Pressure gauge series



## 2" 耐震压力表 LIQUID FILLED PRESSURE GAUGE

型号 MODEL	规格 SPEC	测压范围 PRESSURE	接口尺寸 PORT	精度 PRECISION
YN 50	径向	0.16 0.4 0.6	ZG <sup>1</sup> / <sub>8</sub> "	2.5
YN 50Z	轴向	0.7 1 1.6	ZG <sup>1</sup> / <sub>4</sub> "	
YN 50ZT	轴向带边	2.5 3 4	M14 × 1.5 φ4	
YN 50ZK	轴向插管	6 10 -0.1(Mpa)	φ6	



## 2.5" 耐震压力表 LIQUID FILLED PRESSURE GAUGE

型号 MODEL	规格 SPEC	测压范围 PRESSURE	接口尺寸 PORT	精度 PRECISION
YN 60	径向	0.16 0.4 0.6	ZG <sup>1</sup> / <sub>4</sub> "	2.5
YN 60Z	轴向	0.7 1 1.6	M14 × 1.5	
YN 60ZT	轴向带边	2.5 3 4	φ4	
YN 60ZK	轴向插管	6 10 -0.1(Mpa)	φ6	





## 4" 耐震压力表

### LIQUID FILLED PRESSURE GAUGE

型号 MODEL	规格 SPEC	测压范围 PRESSURE	接口尺寸 PORT	精度 PRECISION
YN 100	径向	0.16 0.4 0.6	ZG1/2"	1.6
YN 100Z	轴向	0.7 1 1.6	M20 × 1.5	
YN 100ZT	轴向带边	2.5 3 4		
		6 10 -0.1(Mpa)		



## 普通压力表

### ORDINARY PRESSURE GAUGE

型号 MODEL	规格 SPEC	测压范围 PRESSURE	精度 PRECISION
Y 40	径向	-0.1-60mpa	1.0 1.6
Y 50	轴向		
Y 60	轴向		2.5 4.0
Y 100	轴向带边		
Y 150			





## 特殊压力表 SPECIAL PRESSURE GAUGE

型号 MODEL	规格 SPEC	测压范围 PRESSURE	接口尺寸 PORT	精度 PRECISION
Y 40	径向	0.16 0.4 0.6	ZG 1/2"	1.6
Y 50	轴向	0.7 1 1.6	M20 x 1.5	
Y 60	轴向带边	2.5 3 4		
Y 100	轴向带边	6 10 -0.1(Mpa)		



# Snowate



**Ms Snow Zhao**  
snow@snowate.com  
snow@membranehousing.org  
Mobile: +86-15030811699  
(WhatsApp, WeChat, Skype, Viber)