

## ELESTAR CATALOGUE

---

Supplier Name: FUJIAN ELESTAR MOTOR CO., LTD.

Address: Office 1301-03, Soho Buliding1#, Taihe City Plaza, Jin'an  
Dist, Fuzhou, Fujian, China

Contact: Miss Linna Zhang

Telephone: 86-591-83929872

Mobile Phone: 86-15059179669

Showroom: <http://elestar.en.made-in-china.com>

01



## Jsl Series Stainless-Steel Self-Priming Pump

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Stainless Steel
Structure	Single-stage Pump
Assembly	Liquid Pumps
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	Automatic Pump
Theory	Jet Pump
Mostor Housing	Aluminumalloy
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Pump Body	Stainless Steel
Impeller	Brass/Techno-Polymer/Stainless Stain
Mechanical	Sic/Ceramic/Graphite

Product Table:

Model	Output Power		Q.max	H. max	S.Head	Speed	Capacity (L/min)	Capacity (L/min)					
	0	10						20	30	40	50		
JSL-08	0.6	0.85	46	47	9	2850	Total head(m)	47	27	20	17	15	13
JSL-10H	0.75	1	52	56				56	38	31	26	22	19
JSL-12H	0.9	1.2	60	60				60	45	37	30	25	22

Model	DIMENSIONS(MM)										PACKING SIZE(MM)			GW	PAC KIN G QTY
	DNA		DNA		A	F	H	H1	N	N1	L	W	H		
	Inch	mm	Inch	mm											
JSL-08	1"	25	1"	25	90	345	174	122	160	120	420	220	230	9.5	1420
JSL-10H	1"	25	1"	25	90	353	174	122	160	120	420	220	230	10.5	
JSL-12H	1"	25	1"	25	90	345	174	122	160	120	420	220	230	11.5	

02



## Jng Cast Iron Self-Priming Pump

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Impeller	Brass/Techno-Polymer/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Mechanical	Sic/Ceramic/Graphite
Protection	IP44/IP54
Cooling	External Ventilation

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
JNG-370	0.37	0.50	40	35	9	1*1"
JNG-550	0.55	0.75	45	40		
JNG-750	0.75	1.00	50	45		
JNG-1100	1.10	1.50	70	55		
JNG-1500	1.50	2.00	80	62		

03



## Js Series Stainless Steel Self-Priming Pump

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$30.00-35.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal

Package: Seaworthy Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Stainless Steel
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Hand Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Motor Housing	Aluminum Alloy
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Pump Body	Stainless Steel
Impeller	Brass/Techno-Polymer/Stainless Stain
Mechanical	Sic/Ceramic/Graphite
Certificate	Ce ,RoHS ,ISO

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch	Packing Size mm
	KW	hp					
JS-60	0.37	0.50	45	38	9	1*1"	415*210*20
JS-80	0.55	0.75	40	40			
JS-100	0.75	1.00	47	45			

04



**Jet-S Series 1HP Self-Priming Electric Water Pump**

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons



## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Jet Pump
Pump Body	Cast Iron
Mostor Housing	Aliuminum Alloy
Impeller	Brass/Techno-Polymer/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Mechanical	Sic/Ceramic/Graphite
Protection	IP44/IP54
Cooling	External Ventilation

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch	Packing Size mm
	KW	hp					
JET-60S	0.46	0.60	40	38	9	1*1"	405*210*220
JET-80S	0.60	0.80	46	45			
JET-100S	0.75	1.00	52	50			

05



Jet-L 100% Copper Wire  
Self Priming Electric  
Water Pump with Brass  
Impeller

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Shaft	Carbon Steel/Stainless Steel
Impeller	Brass/Techno-Polymer/Stainless Stain
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Mechanical	Sic/Ceramic/Graphite

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch	Packing Size mm
	kw	hp					
JET-60L	0.46	0.60	42	38	9	1*1"	475*210*220
JET-80L	0.60	0.80	48	46			
JET-100L	0.75	1.00	52	51			

06



## Jet-M High Efficiency Single Phase AC Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Impeller	Brass/ PPO/Stainless Steel
Wire	Copper/Aluminium
Shaft	Stainless Steel /Steel
Certificate	Ce, RoHS, ISO
Frequency	50Hz/60Hz
Voltage	220V/110V
Protection	IP44/IP54

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
JET-100A	0.10	0.13	40	35	9	1*1"
JET-60M	0.46	0.60	42	38		
JET-80M	0.60	0.80	48	46		
JET-100M	0.75	1.00	52	51		
JET-120M	1.10	1.50	55	60		
JET-140M	1.50	2.00	60	70		

07



Jsp-6m Series 0.5HP Self-Priming Electric Water Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminium Alloy
Impeller	Brass/Techno-Polymer/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Mechanical	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Certificate	Ce/ISO/RoHS
Wire	Copper /Aluminium

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch	Packing Size mm
	kw	hp					
JSP-10H/M	0.75	1.00	50	56	9	1*1"	475*210*230
JSP-12H/M	0.90	1.25	50	64			
JSP-15H/M	1.10	1.50	50	70			

08



Jet-100p Series Widely  
Used in Domestia and  
Civilarea Plastic

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$30.00-35.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons



## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Plastic
Structure	Single-stage Pump
Assembly	Liquid Pumps
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Jet Pump
Pump Body	Plastic
Motor Housing	Aluminumalloy
Impeller	Brass/Techno-Polymer/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Mechanical	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation

Product Table:

Model	Output Power		Q. max	H. max	S.H ead	Spe ed	Capacity (L/min)											
	KW	HP						0	5	10	15	20	25	30	35	42	46	52
JET-60P7	0.3	0.5	42	40	9	2850	Total head(m)	40	36	32	29	26	24	20	13	5	-	-
JET-80P5	0.5	0.75	46	45	9	2850		45	42	38	35	31	28	25	22	12	5	-
JET-100P5	0.75	1	52	50	9	2850		50	46.5	43	39	36	32	29	26	14	8	5

09



**Automatic Booster  
Stainless Steel Jet Water  
Pump with 24L Pressure  
Tank**

[Contact Supplier](#)

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	100+	US \$50.00-60.00

Port: Fuzhou

Payment: L/C, T/T, Western Union, Paypal, Money Gram

Package: Carton

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Multistage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Submersible Pump
Industry	Mechanical Pump
Media	Centrifugal Pump
Performance	No Leakage Pump
Theory	Jet Pump
Pump Body	Stainless Steel
Impeller	Brass/Techno-Polymer(P.P.O)/Stainless Steel
Mechanical Seal	Sic/Ceramic/Graphite
Protection	IP44/IP45
Cooling	External Ventilation

Product Table:

Model	Power		Max.Flow l/min	Max.Hea d m	Max.suct m	In/out let inch	Weight kgs	Packing Size mm
	KW	HP						
AUQB60	0.37	0.5	35	32	8	1*1	8	490*320* 540
AUJS-100	0.75	1	52	50	9	1*1	19	490*320* 590
AUJET-100S	0.75	1	52	50	9	1*1	19	490*320* 590
AUJET-100L	0.8	1.1	52	51	9	1*1	15	490*320* 590
AUDP505 A	1.1	1.5	80	60	9	1*1	30	490*320* 590

010



Elestar Surface Self-Priming Water Pump with Ce Approved (JET-B)

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$30.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Seaworthy Cartons

Product Attribute:	Certification	CE, ISO
	Installation Method	Horizontal
	Power	Electric
	Material	Cast Steel
	Working Fluid	Water
	Performance	No Leak
	Applications	Petrochemical
	Impeller	Brass/Techno-Polymer(P.P.O)/Stainless Steel
	Pump Body	Cast Iron
	Mechanical Seal	Sic/Ceramic/Graphite
	Cooling	External Ventilation
	Insulation Class	B/F
	Motor Housing	Aluminum Alloy
	Protection Class	IP44/IP45
	Shaft	Carbon Steel/Stainless Steel

## ELESTAR CATALOGUE

Product Table:

Model	Output Power		Q.max (L/min)	H.max (m)	S.Head (m)	Speed (r/min)
	KW	HP				
JET-60B	0.37	0.5	42	40	9	2850
JET-80B	0.55	0.75	48	48	9	2850
JET-100B	0.75	1	54	52	9	2850
JET-110B	1	1.3	54	54	9	2850

  

MODEL	DIMENSIONS(mm)				PACKING SIZE(mm)			G.W	PACKIN G QTY.
	DNA		DNM		L	W	H	KG	20''(Con t)
	Inch	mm	Inch	mm					
JET-60B	1''	25	1''	25	420	220	220	15.3	1340
JET-80B	1''	25	1''	25	420	220	220	15.7	1340
JET-100B	1''	25	1''	25	420	220	220	16.9	1340
JET-110B	1''	25	1''	25	420	220	220	17.4	1340

011



High Quality Clean Water  
Pump for Domestic Use  
Qb60 Series

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram, Cash or Alipay

Package: Seaworthy Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Peripheral
Assembly	Booster Pump
Power	Electric
Start Up	Hand Pump
Type	Peripheral Pump
Application	Peripheral Pump
Industry	Domestic Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Vortex Pump
Motor Housing	Aluimum Motor House
Insulation Class	B / F
Impeller	Brass
Pump Body	Cast Iron
Shaft	45#Steel/Stainless Steel
Protection	IP44/IP54
Motor Phase	Single Phase

Product Table:

Model	Power		Max. Flow	Max. Head	Max. Suct	In/out let	Packing Size
	Kw	HP	L/min	M	M	Inch	mm
QB-60	0.37	0.50	40	40	9	1*1"	278*143*173
QB-70	0.55	0.75	45	50			
QB-80	0.75	1.00	50	55			
QB-90	1.10	1.50	80	70			

012



**dB-550A Series Peripheral Pump Water Pump**

[Contact Supplier](#)

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons



## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Peripheral Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Mechanical	Sic/Ceramic/Graphite
Protection	IP44/IP54
Cooling	External Ventilation

Product Table:

Model	Power		Max.Flow	Max.Head	Max.suct	In/out let	Packing Size
	kw	hp	l/in	m	m	inch	mm
DB-125A	0.125	0.16	35	30	9	1*1"	275*155*167
DB-330A	0.37	0.50	35	35			
DB-550A	0.55	0.75	45	50			
DB-750A	0.75	1.00	50	55			

013



Jfb Series 1HP Peripheral Water Pump for House

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

# ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Peripheral Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Impeller	Brass/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Mechanical	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Certificate	Ce ISO9001

Product Table:

Model	Output Power		Q. max	H. max	S.Head	Speed	Capacity (L/min)											
	KW	HP					0	5	10	15	20	25	30	35	40	45	50	
JFB-370	0.37	0.5	40	38	9	2850	Total head(m)	38	27	23	19	15	11	7	3	-	-	-
JFB-550	0.55	0.75	50	45	9	2850		45	32	28	24	20	15	10	5	-	-	-
JFB-750	0.75	1	60	60	9	2850		60	44	39	34	27.5	22.5	18	14	9	5	5

ELESTAR CATALOGUE

Model	DIMENSIONS(MM)																			PACKING SIZE(MM)			G W	PACKING QTY	
	DNA		DNA		a	f	h1	h2	h3	h4	m1	m2	n1	n2	b	s	l2	w	g	L	W	H	KG		22"
	Inch	mm	Inch	mm																					
JFB-370	1"	25	1"	25	24	24 4	63	90	10 8	16 0	96	80	12 2	10 0	22	7	58	80	8	28 0	14 5	18 0	2.8	33 00	
JFB-550	1"	25	1"	25	24	24 4	63	90	10 8	16 0	96	80	12 2	10 0	22	7	58	80	8	31 0	18 0	20 0	9.7	33 00	
JFB-750	1"	25	1"	25	24	27 8	71	10 0	18 2	18 2	10 6	90	13 4	11 2	22	7	63	93	10	31 0	18 0	20 0	10.5 8	33 00	

014



## Jfb-550 Series Peripheral Pump for Water Pump

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Peripheral Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Impeller	Brass/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Mechanical	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Certificate	Ce ,RoHS ,ISO
Color	as You Like

Product Table:

Model	Output Power		Q. max	H. max	S.Head	Speed	Capacity (L/min)											
	KW	HP					0	5	10	15	20	25	30	35	40	45	50	
JFB-370	0.37	0.5	40	38	9	2850	Total head(m)	38	27	23	19	15	11	7	3	-	-	-
JFB-550	0.55	0.75	50	45	9	2850		45	32	28	24	20	15	10	5	-	-	-
JFB-750	0.75	1	60	60	9	2850		60	44	39	34	27.5	22.5	18	14	9	5	5

ELESTAR CATALOGUE

Model	DIMENSIONS(MM)																			PACKING SIZE(MM)			G W	PACKING QTY
	DNA		DNA		a	f	h1	h2	h3	h4	m1	m2	n1	n2	b	s	l2	w	g	L	W	H		
	Inch	mm	Inch	mm																				
JFB-370	1"	25	1"	25	24	24.4	63	90	108	160	96	80	122	100	22	7	58	80	8	280	145	180	2.8	3300
JFB-550	1"	25	1"	25	24	24.4	63	90	108	160	96	80	122	100	22	7	58	80	8	310	180	200	9.7	3300
JFB-750	1"	25	1"	25	24	27.8	71	100	182	182	106	90	134	112	22	7	63	93	10	310	180	200	10.58	3300

015



High Quality Electric  
Clean Water Pump for  
Garden Use Idb

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram, Cash or Alipay

Package: Seaworthy Cartons



## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Peripheral
Assembly	Booster Pump
Power	Electric
Start Up	Hand Pump
Type	Peripheral Pump
Application	Peripheral Pump
Industry	Domestic Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Vortex Pump
Motor Housing	Aluinium Motor House
Insulation Class	B / F
Impeller	Brass
Pump Body	Cast Iron
Shaft	45#Steel/Stainless Steel
Protection	IP44/IP54
Motor Phase	Single Phase

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
IDB-35	0.37	0.50	40	40	9	1*1"
IDB-40	0.55	0.75	45	50		
IDB-50	0.75	1.00	50	55		
IDB-60	1.10	1.50	80	70		

016



## Gp Series Quality Self-Sucking Water Pump

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

# ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	<50 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Self-Sucking Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Shaft	Carbon Steel/Stainless Steel
Mechanical Seal	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation

Product Table:

Model	Output Power		Q.m ax	H. max	S.He ad	Spe ed	Total head(m)	Capacity (L/min)								
	0	5						10	15	20	25	30	35	40		
GP-125A	0.125	0.16	35	35	9	2850	35	35	31	27	23	18	13.5	9	5	.
GP-250A	0.28	0.5	40	35				35	32	29	26	21.8	17.5	13.5	9.5	5

Model	DIMENSIONS(MM)															PACKING SIZE(MM)			G. W	PA CKI NG QT Y.	
	DNA		DNA		A	B	C	D	E	F	G	H	I	J	K	L	L	W			H
	Inc h	m	Inc h	m																	
GP-125A	1"	25	1"	25	211	86	71	202	40	143	119	105	9	213	83	40	260	200	240	6.6	2100
GP-250A					211	86	71	202	40	143	119	105	9	213	83	40	260	200	240	7	2100

017



Zdb Series Electric Water Pump Self-Priming Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

# ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Type	Peripheral Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Impeller	Brass/ Stainless Steel
Shaft	Carbon Steel/Stainless Steel
Instulation	Class B/ Class F
Mechanical Seal	Sic/ Ceramic/Graphite
Protection	IP44/IP54
Cooling	External Ventilation

Product Table:

Model	Output Power		Q.max	H. max	S.Head	Speed	Total head(m)	Capacity (L/min)					
								0	10	20	30	40	50
ZDB35	0.37	0.5	35	35	9	2850	35	27	20	17	15	13	
ZDB45	0.55	0.75	46	47				47	38	31	26	22	19
ZDB65	0.75	1	52	56				56	45	37	30	25	22

Model	DIMENSIONS(MM)												PACKING SIZE (MM)			G.W	PACKING QTY			
	DNA		DNA		A	B	C	D	E	H	H1	H2	L	L	W			H	KG	20"
	Inc h	mm	Inc h	mm																
ZD B35	1"	25	1"	25	85	100	60	106	25	207	67	195	236	285	201	250	8.5	2258		
ZD B45					95	125	62	106	25	224	80	217	262	305	215	275	10.5	1608		
ZD B65					95	125	62	106	25	225	80	217	262	305	215	275	12	1608		

018



TPS Series Self-Sucking  
Peripheral Pump Clean  
Water Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$15.00-30.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Submersible Pump, Clarified Water Pump, Sewage Pump
Industry	Mechanical Pump
Media	Sewage Pumps
Performance	Automatic Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Shaft	Carbon Steel/Stainless Steel
Motor Housing	Aluminum Alloy
Mechanical	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Certificate	Ce&RoHS

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
TPS-60	0.37	0.50	40	35	9	1*1"
TPS-70	0.55	0.75	45	50		
TPS-80	0.75	1.00	50	55		

019



Self-Sucking Water  
Pumps Peripheral Pump  
(Wz)

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons



# ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	<50 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Peripheral Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Mechanical	Sic/Ceramic/Graphite
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Certificate	Ce, RoHS, ISO

Product Table:

Model	Output Power		Q.m ax	H. max	S.He ad	Spee d	Capacity (L/min)									
	KW	HP					0	5	10	15	20	25	30	32		
AU WZ-125	0.37	0.5	35	30	9	2850	Total head (m)	30	26	20	13	10	4	3	2	
WZ-125	0.37	0.5	35	30	9	2850		30	26	20	13	10	4	3	2	

  

Model	DIMENSIONS(MM)												PACKING SIZE(MM)			GW	PA CKI NG QTY	
	DNA		DNA		a	b	c	d	e	f	g	h	i	L	W			H
	Inc h	mm	Inc h	mm														
AU WZ-125	1"	25	1"	25	277	116	84.4	287	97.5	10	140	114	172	313	187	300	9	1630
WZ-125	1"	25	1"	25	277	116	84.4	287	97.5	10	140	114	172	313	170	170	7.2	3000

020



0.5HP Small Size Homeuse Vortex Water Pumps for Homeuse (WZB)

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$17.20-30.50

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram, Cash or Alipay

Package: Seaworthy Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	<50 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Self-Sucking Pump
Application	Self-Sucking Pump
Industry	Domestic Pump
Media	Clean Water Pump
Performance	Automatic Pump
Theory	Self-Sucking Pump
Motor Housing	Aluminum Motor House
Insulation Class	B / F
Impeller	Brass
Pump Body	Cast Iron
Shaft	45#Steel/Stainless Steel
Protection	IP44/IP54
Motor Phase	Single Phase

Product Table:

Model	Power		Max.Flow m <sup>3</sup> /h	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
WZB125	0.125		1.8	24	9	1*1"
WZB250	0.25		2.0	28		
WZB370	0.37		2.2	32		
WZB550	0.55		2.8	38		
WZB750	0.75		3.0	44		
WZB1100	1.10		4.5	50		

021



2HP Electric Cast Iron  
Centrifugal Pump Clean  
Pump (Dtm-20)

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

# ELESTAR CATALOGUE

Product Attribute:

Max.Head	10-30m
Max.Capacity	300-400 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Centrifugal Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Impeller	Brass/Techno-Polymer/Stainless Stain
Motor Housing	Aluminum Alloy
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Mechanical	Sic/Ceramic/Graphite

Product Table:

Model	Output Power		Q.max	H. max	S.Head	Speed	Capacity (L/min)						
	KW	HP					0	100	200	300	400	500	
DTM-18	0.75	1	220	14	9	2850	Total head(m)	14	13	3	-	-	-
DTM-18	0.75	1	300	14	9	2850		14	13	10.5	7	-	-
DTM-20	1.1	1.5	400	18	9	2850		18	16	15	13	8	-
DTM-20	1.5	2	500	18	9	2850		18	16	15	16.5	14	12

Model	DIMENSIONS(MM)												PACKING SIZE(MM)			GW	PACKING QTY
	DNA		DNA		a	b	c	d	e	f	g	h	L	W	274		
	Inch	mm	Inch	mm													
DTM-18	1.5"	40	1.5"	40	320	190	242	100	28	92	54	10	360	213	274	17	1200
DTM-18	2"	50	2"	50	375	205	260	160	31	68	95	10	360	213	275	28	1200
DTM-20	1.25"	40	1.5"	40	375	205	260	160	31	68	95	10	385	213	275	20	1200
DTM-20	2"	50	2"	50	395	238	315	190	35	121	66	10	385	213	275	27.5	1200

022



**CMH8 Hot Pump Series  
Horizontal Multi-Stage  
Centrifugal Pump New**

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Multistage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Centrifugal Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Sewage Pumps
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Impeller	Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Mechanical	Ceramic/Graphite

023



**Dk Series Centrifugal Pump for Urban Water Supply**

[Contact Supplier](#)

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons



## ELESTAR CATALOGUE

Product Attribute:

Max.Head	10-30m
Max.Capacity	200-300 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Centrifugal Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Aluminum Alloy
Impeller	Brass/Techno-Polymer/Stainless Stain
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Mechanical	Sic/Ceramic/Graphite

Product Table:

MODEL	INPUT MAX	OUTPUT POWER	CURRENT	Q.MAX	H.MAX	SUCT.MAX	DNA/DNM
DK-20	1.1KW	1HP/0.75KW	5.2A	180L/MIN	20M	9M	1.5 /40mm

024



## Cpm Series Single Stage Centrifugal Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

# ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	100-200 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Submersible Pump, Clarified Water Pump
Industry	Mechanical Pump
Media	Sewage Pumps
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Wire	Copper/Aluminium
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Mechanical	Sic/Ceramic/Graphite
Impeller	Brass
Certificate	Ce&RoHS
Frequency	50Hz/60Hz

Product Table:

Model	Output Power		Q. max	H. max	S.H ead	Speed	Capacity (L/min)										
	KW	HP					0	20	40	60	80	90	95	110	150	180	200
CP M-130	0.3	0.5	90	18	9	2850	Total head(m)	18	16	15	10	5	-	-	-	-	-
CP M-146	0.5	0.7	100	28	9	2850		25	23.5	21.3	17.3	12	9	7	-	-	-
CP M-158	0.7	1	110	32	9	2850		32	30	27.5	24	19	16	14	8	-	-
CP M-180	1.1	1.5	130	34	9	2850		34	32	31.5	29	26	23	20	14	11	8
CP M-200	1.5	2	150	37	9	2850		37	35	33	30	27	24	21	15	12	9

025



1.2"\*1.25" Pipe Mh Series  
Horizontal Multi-Stage  
Centrifugal Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Stainless Steel
Structure	Multistage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Submersible Pump, Clarified Water Pump
Industry	Mechanical Pump
Media	Sewage Pumps
Performance	Automatic Pump
Theory	Centrifugal Pump
Frquency	50Hz/60Hz
Pump Body	Stainless Steel/Cast Iron
Cooling	External Ventilation
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Mechanical	Sic/Ceramic/Graphite
Impeller	Stainless Steel/PPO

Product Table:

Model PIPE= 1.25"* 1.25"	Output Power	Voltage		Current		Input Power		Capac ity	0	24	40	48
		50HZ	50HZ	220V	380V				0	1.44	2.4	2.88
MH37 0-1.25	0.7	220	380	2.9	1.5	0.8	0.8	Total head( m)	26.5	23	19	-
MH55 0-1.25	0.55	220	380	4.5	1.9	1	0.9		38.5	32.5	27	17
MH75 0-1.25	0.75	220	380	5.8	2.3	1.2	1.1		50	45.5	38	24.5
MH92 0-1.25	0.92	220	380	6.4	2.5	1.4	1.3		67	59	48.5	41.5

026



Scm-26st Series Stainless Steel Water Pump  
Centrifugal Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$30.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal

Package: Sea Worthy Carton (with Foam )

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	10-30m
Max.Capacity	100-200 L/min
Driving Type	Motor
Material	Stainless Steel
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Jet Pump
Application	Submersible Pump
Industry	Mechanical Pump
Media	Sewage Pumps
Performance	Automatic Pump
Theory	Centrifugal Pump
Pump Body	Stainless Steel
Impeller	Brass/Techno-Polymer/Stainless Steel
Shaft	Carbon Steel /Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Certificate	Ce, RoHS, ISO
Frequency	50Hz/60Hz
Voltage	220V/110V

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch	Packing Size mm
	kw	hp					
SCM-18ST	0.37	0.50	110	18	9	1*1"	335*230*273
SCM-20ST	0.55	0.75	130	20			
SCM-26ST	0.75	1.00	145	26			
SCM-34ST	1.00	1.50	190	34			

027



Nfm Series Centrifugal Pump Industrial Use and Urban Water Supply

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons



## ELESTAR CATALOGUE

Product Attribute:

Max.Head	10-30m
Max.Capacity	>400 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Centrifugal Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Impeller	Brass/Techno-Polymer/Stainless Stain
Motor Housing	Aluminum Alloy
Shaft	Carbon Steel/Stainless Steel
Insulation	Class B/Class F
Protection	IP44/IP54
Cooling	External Ventilation
Mechanical	Sic/Ceramic/Graphite

Product Table:

Model	Power	Q.Max(l/min)	H.max(m)	Pipe Dia	L*W*H(mm)	N.W(kg)
NFM-128A	1hp/0.75kw	220	13	1.5*1.5	350*180*215	13.2
NFM-130C	1.5hp/1.1kw	380	15	2*2	370*210*250	18.1
NFM-130B	2hp/1.5kw	400	17	2*2	370*210*250	19.3
NFM-130A	3hp/2.2kw	11000	18	3*3	435*265*350	41

028



Scm2-60A Series High Efficiency Centrifugal Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	100-200 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Centrifugal Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Impeller	Brass/Techno-Polymer/Stainless Stain
Motor Housing	Aluminium Alloy
Insulation	Class B/Class F
Protection	IP44/IP54
Mechanical	Sic/Ceramic/Graphite
Cooling	External Ventilation

Product Table:

Model	Output Power		Q.m ax	H. max	S.H ead	Spe ed		Capacity (L/min)									
								0	20	40	60	80	100	110	120	130	140
SC M2-45	0.75	1	90	35	9	2850	Total head(m)	35	31	27	22	15	-	-	-	-	-
SC M2-52	1.1	1.5	105	45				45	41	37	62	25	17	-	-	-	-
SC M2-60A	1.5	2	105	55				55	50	45	40	32	23	20	10	-	-
SC M2-60B	1.5	2	130	55				55	52	49	44	37	31	28	25	20	-
SC M2-68	2.2	3	150	66				66	62	59	55	50	42	39	35	30	25

ELESTAR CATALOGUE

Model	DIMENSIONS(MM)												PACKING SIZE(MM)			GW	PACKING QTY	
	DNA		DNA		a	b	c	d	e	f	g	h	i	L	W	H		KG
	Inc h	mm	Inc h	mm														
SC M2-45	1.25"	30	1"	25	379	135	110	153	84	263	225	185	11	210	380	240	18	1100
SC M2-52	1.25"	30	1"	25	400	140	115	148	86	256	210	165	10	420	251	323	23.5	820
SC M2-60A	1.25"	30	1"	25	400	140	115	148	86	256	210	165	10	420	251	323	25	820
SC M2-60B	1.5"	40	1.5"	40	400	140	115	148	86	256	210	165	10	420	251	323	25	820
SC M2-68	1.5"	40	1.25"	30	450	160	140	175	90	320	240	200	14	480	290	350	31	650

029



## Horizontal Multi-Stage Centrifugal Water Pump (CMF4)

[Contact Supplier](#)

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	100+	US \$38.00-50.00

Port: Fuzhou

Payment: L/C, T/T, Western Union, Paypal, Money Gram

Package: Carton

Product Attribute:	Max.Head	10-30m
	Max.Capacity	50-100 L/min
	Driving Type	Motor
	Material	Stainless Steel
	Structure	Multistage Pump
	Assembly	Booster Pump
	Power	Electric
	Start Up	Electric Pump
	Type	Jet Pump
	Application	Submersible Pump
	Industry	Mechanical Pump
	Media	Centrifugal Pump
	Performance	No Leakage Pump
	Theory	Centrifugal Pump
	Pump Body	Stainless Steel
	Impeller	Brass/Techno-Polymer(P.P.O)/Stainless Steel
Mechanical Seal	Sic/Ceramic/Graphite	
Protection	IP44/IP45	
Cooling	External Ventilation	

## ELESTAR CATALOGUE

Product Table:

Model	Dimensions(mm)				Weight (kg)
	Single phase		Three phase		
	L1	H	L1	H	
CFM4-20(T)	400	217	400	214	9.7
CFM4-30(T)	400	217	400	214	11
CFM4-40(T)	400	217	400	214	11.5
CFM4-50(T)	400	217	400	214	12.5
CFM4-60(T)	400	217	400	214	13.5

  

Model	Output Power km	Rate flow m <sup>3</sup> /h	Rate head m
CFM4-20(T)	0.55	4	15
CFM4-30(T)	0.75	4	22
CFM4-40(T)	0.75	4	30
CFM4-50(T)	1	4	38
CFM4-60(T)	1.1	4	45

030



## Jdw Series Self-Priming Deep-Well Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	100-200 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Deep-Well Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Motor Housing	Aluminum Alloy
Shaft	Carbon Steel AISI 145
Insulation	Class B/Class F
Protection	IP44/IP54
Pump Body	Cast Iron
Impeller	Brass/Techno-Polymer/Stainless Stain
Mechanical	Sic/Ceramic/Graphite
Cooling	External Ventilation

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
JDW-370	0.37	0.5	42	15	9	1*1"
JDW-550	0.55	0.75	45	20		
JDW-750	0.75	1	50	25		



031



DP Powered Electrical Water Pump for Industrial

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	30-50m
Max.Capacity	50-100 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	DELL-Well Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Impeller	Brass/Techno-Polymer /Stainless Steel
Mechanical	Sic/Ceramic/Graphite
Motor	Closed, Externally Entilatated
Shaft	Carbon Steel AISI1045
Insulation	Class B/Class F
Protection	IP44/IP54

Product Table:

Model	Power		Max.Flow l/min	Max.Head m	Max.suct m	In/out let inch
	kw	hp				
DP-370	0.37	0.5	25	15	9	1*1"
DP-550	0.55	0.75	30	20		
DP-750	0.75	1	35	25		
DP-1100	1.1	1.5	40	20		
DP-1500	1.5	2	45	25		

032



3 HP Cab Series Self-Priming Deep-Well Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$25.00-50.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

## ELESTAR CATALOGUE

Product Attribute:

Max.Head	50-80m
Max.Capacity	100-200 L/min
Driving Type	Motor
Material	Cast Iron
Structure	Single-stage Pump
Assembly	Booster Pump
Power	Electric
Start Up	Electric Pump
Type	Deep-Well Pump
Application	Clarified Water Pump
Industry	Mechanical Pump
Media	Clean Water Pump
Performance	No Leakage Pump
Theory	Centrifugal Pump
Pump Body	Cast Iron
Motor Housing	Closed Externally Ventilated
Shaft	Carbon Steel AISI 1045
Impeller	Brass/Techno-Polymer/Stainless Stain
Mechanical	Sic/Ceramic/Graphite
Insulation	Class B/Class F
Protection	IP44/IP54
Flow	90-140L/M

Product Table:

Model	Output Power		Q.m ax	H. max	S.He ad	Spe ed		Capacity (L/min)								
	KW	HP						0	20	30	50	70	90	110	130	140
CAB 150	1.1	1.5	92	61	9	2850	Total head(m)	61	56.2	54	48	41	32	-	-	-
CAB 200	1.5	2	110	62.5				62.5	59.5	58	54	49	42.5	34	-	-
CAB 300	2.2	3	140	64.5				64.5	62	60.5	27	52.5	47	42	35	32

033

24L Spherical Tank /  
Water Pressure Tank



Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$3.00-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

Product Attribute:	Function	Storage Pressure Vessel, Pressure Tank
	Application	Liquid
	Material	Carbon Steel
	Storage Medium	Clean Water
	Body	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Flange	Carbon Steel/Stainless Steel

Product Table:	Item	Pressure Tank					
	Material	Carbon Steel					
	Membrane	EPDM/Rubber/Butyl					
	Application	Water pressure constant					
	Certificate	CE/ISO					
	OEM and ODM	Wellcome					
	Capacity	1L-19L					
	Code	Capacity Ltr	Gallons	Package(cm)	Max.Press.	Max.temp.	Connect
	CF-24*	24L	6.34	35*35*31	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
	RF-24*	24L	6.34	35*35*35	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"

034



5-100L Stainless Steel Horizontal Water Storage Pressure Tank

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$3.00-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

Product Attribute:	Function	Storage Pressure Vessel, Pressure Tank
	Application	Liquid
	Material	Carbon Steel
	Pressure	0.1MPa≤p<1.6MPa
	Body	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Certificate	EMC/Ce/RoHS

Product Table:	Item	Pressure Tank
	Material	Stainless Steel
	Membrane	EPDM/Rubber/Butyl
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	1L-19L

# ELESTAR CATALOGUE

SV-5	5L	1.32	18*18*29	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-8	8L	2.11	20*20*32	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-12	12L	3.17	28*28*38	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-19	19L	5.02	27*27*40	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-24	24L	6.34	27*27*45	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-36	36L	9.25	36*36*57	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-50	50L	13.2	36*36*71	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-60	60L	15.8	45*45*63	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-80	80L	21	45*45*75	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
SV-100	100L	26.4	45*45*88	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"

035



Pressure Tank for Auto Water Pump



Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$3.00-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

Product Attribute:	Application	Liquid
	Material	Carbon Steel
	Pressure	0.1MPa≤p<1.6MPa
	Storage Medium	Clean Water
	Body	Carbon Steel
	Membrane	EPDM/Rubber/Butyl

Product Table:	Item	Pressure Tank
	Material	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	1L-19L



## ELESTAR CATALOGUE

Code	Capacity Ltr	Gallons	Package(cm)	Max.Press.	Max.temp.	Connect
VT-5	5L	1.32	18*18*29	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-5-1*	5L	1.32	15.5*15.5*30	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-8	8L	2.11	20*20*32	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-12	12L	3.17	27*27*30	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-19	19L	5.02	27*27*40	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-24	24L	6.34	27*27*45	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"

036



Horizontal Type Pressure Tank (24L)

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$3.00-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

Product Attribute:	Application	Liquid
	Material	Carbon Steel
	Pressure	0.1MPa≤p<1.6MPa
	Storage Medium	Clean Water
	Pressure Level	Low Pressure (0.1MPa≤p<1.6MPa)
	Membrane	EPDM/Rubber/Butyl

Product Table:	Item	Pressure Tank
	Material	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	1L-100L
	Working temperature:	0-99°C
	Working pressure:	5-8bar

037



19-50L Carbon Steel Horizontal Pressure Tank



Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	500+	US \$9.00-18.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

Product Attribute:	Function	Storage Pressure Vessel, Pressure Tank
	Application	Liquid
	Material	Carbon Steel
	Pressure	0.1MPa≤p<1.6MPa
	Membrane	EPDM/Rubber/Butyl
	Certificate	EMC/Ce/RoHS
	Flange	Carbon Steel/Stainless Steel
	Color	Red/Blue

Product Table:	Item	Pressure Tank
	Material	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	19L-50L
	Working temperature:	0-99°C
	Working pressure:	5-8bar

## ELESTAR CATALOGUE

Code	Capacity Ltr	Gallons	Package(cm)	Max.Press.	Max.temp.	Connect
HT-19	19L	5.2	40*27*31	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
HT-24	24L	6.3	45*27*31	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
HT-36	36L	9.5	41*36*39	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
HT-50	50L	13.2	55*36*39	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"

038



Stainless Steel /Carbon Steel Horizontal Type



Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$5.00-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Cartons

Product Attribute:	Certificate	Ce, RoHS, ISO
	Type	Vertical
	Body	Stainless Steel
	Membrane	Rubber/EPDM/Butyl
	Volume	5L-100L

Product Table:	Item	Pressure Tank
	Material	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	1L-100L
	Working temperature:	0-99°C
	Working pressure:	5-8bar

039



Elestar Vertical Type of Pressure Tank for Water Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$15.00-30.00

Port: Ningbo

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Carton

Product Attribute:	Function	Storage Pressure Vessel
	Application	Liquid
	Material	Carbon Steel
	Pressure	0.1MPa≤p<1.6MPa
	Pressure Level	Low Pressure (0.1MPa≤p<1.6MPa)
	Condition	New
	Max Working Remperature	0-99 Degrees Celsius
	Membrane	Natural Rubber /EPDM/Butyl

Product Table:	Item	Pressure Tank
	Material	Stainless Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	19-100L
	Working temperature:	0-99°C
	Working pressure:	5-8bar

ELESTAR CATALOGUE

VT-5	5L	1.32	18*18*29	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VTL-5	5L	1.32	15.5*15.5*30	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-8	8L	2.11	20*20*32	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-12	12L	3.17	27*27*30	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-19	19L	5.02	27*27*40	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-24	24L	6.34	27*27*45	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-36	36L	9.25	36*36*41	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VTL-36	36L	9.25	36*36*57	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VTL-50	50L	13.2	36*36*71	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VTL-60	60L	15.8	39*39*83	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VTL-60-1	60L	15.8	45*45*63	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-80	80L	21.1	45*45*75	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-100	100L	26.4	45*45*88	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"

040

Carbon Steel Expansion Tank for Water Pump



FUJIAN ELESTAR MOTOR CO., LTD.

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$7.00-27.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Carton

Product Attribute:	Function	Reaction Pressure Vessel
	Application	Liquid
	Material	Carbon Steel
	Pressure	1.6MPa≤p<10.0MPa
	Storage Medium	Moncombustible/Nontoxic
	Pressure Level	Low Pressure (0.1MPa≤p<1.6MPa)
	Condition	New

Product Table:	Item	Pressure Tank
	Material	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	1L-100L
	Working temperature:	0-99°C
	Working pressure:	5-8bar



041



High Pressure Tank for Auto Water Pump

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	100+	US \$3.00-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram, Cash or Alipay

Package: Seaworthy Cartons

Product Attribute:	Function	Storage Pressure Vessel, Pressure Tank
	Application	Liquid
	Material	Carbon Steel
	Pressure	0.1MPa≤p<1.6MPa
	Storage Medium	Clean Water
	Pressure Level	Low Pressure (0.1MPa≤p<1.6MPa)
	Condition	New
	Body	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Certificate	EMC/Ce/RoHS
	Color	Red
	Flange	Carbon Steel/Stainless Steel

Product Table:	Item	Pressure Tank
	Material	Carbon Steel
	Membrane	EPDM/Rubber/Butyl
	Application	Water pressure constant
	Certificate	CE/ISO
	OEM and ODM	Wellcome
	Capacity	1L-19L

## ELESTAR CATALOGUE

Code	Capacity Ltr	Gallons	Package(cm)	Max.Press.	Max.temp.	Connect
VT-5	5L	1.32	18*18*29	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-5-1*	5L	1.32	15.5*15.5*30	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-8	8L	2.11	20*20*32	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-12	12L	3.17	27*27*30	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-19	19L	5.02	27*27*40	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"
VT-24	24L	6.34	27*27*45	5-8bar/72.5-116psi	77-99°C	G1"/G3/4"

042



Ce Accessories Automatic Pressure Controller for Water Pump PC-3

Contact Supplier

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	600+	US \$11.20-13.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Carton

Product Table:	Descriptions:	
	Rated Voltage	110V/230V
	Max. Current	10(6)A
	Frequency	60HZ/50HZ
	Max. Power	1.1KW/2.2KW
	Joint Screw	G1
	Starting Pressure	1.5bar/2.2bar
	Max Working Pressure	10bar
	Protection Grade	IP65
	Max Operating Temperature	60 degree
	Application	Self-Priming Pump/Jet Pump/Garden Pump/Clarified water Pump
	Function:	
	1. Start and stop the pump automatically	
	2. Protect the pump from damage caused by dry-running	

043



Ce Accessories Automatic Pressure Controller for Water Pump PC-1A

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	600+	US \$11.20-13.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Carton

044



**CE Automatic Pressure Pump Controller for Water Pump PC-4b**

**Contact Supplier**

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	600+	US \$10.55-11.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Carton

Product Table:	Descriptions:	
	Rated Voltage	110V/230V
	Max. Current	16(8)A
	Frequency	60HZ/50HZ
	Max. Power	1.1KW
	Starting Pressure	1.1bar/2.2bar
	Max Working Pressure	10bar
	Protection Grade	IP65
	Max Operating Temperature	60 degree
	Application	Self-Priming Pump/Jet Pump/Garden Pump/Clarified water Pump
	Function:	
	1. Start and stop the pump automatically	
	2. Protect the pump from damage caused by dry-running	

045



Accessories Automatic Pressure Control for Water Pump PC-4A

Contact Supplier

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	600+	US \$10.55-11.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Carton

Product Table:	Descriptions:	
	Rated Voltage	110V/230V
	Max. Current	10(6)A
	Frequency	60HZ/50HZ
	Max. Power	1.1KW/2.2KW
	Joint Screw	G1
	Starting Pressure	1.5bar/2.2bar
	Max Working Pressure	10bar
	Protection Grade	IP65
	Max Operating Temperature	60 degree
	Application	Self-Priming Pump/Jet Pump/Garden Pump/Clarified water Pump
	Function:	
	1. Start and stop the pump automatically	
	2. Protect the pump from damage caused by dry-running	

046



## Stainless Steel Pressure Gauge-Bottom Pressure Gauge

[Contact Supplier](#)

Price:	<b>Min. Order(Pieces)</b>	<b>FOB Price</b>
	1,000+	US \$0.75-1.20

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Export Standard Box

Product Attribute:	Measuring Range	Low-pressure Gauge
	Type	General Pressure Gauge
	Accuracy	1.6
	Display	Pointer
	Application	Domestic
	Structure	Bourdon Tube
	Connection Type	Radial Direction
	Function	Local Indication Type, Electric Signal-controlled
	Installation Structure	Direct Mounting
	Features of Measurement Medium	General Pressure Gauge
	Indicating Pressure Reference	General Pressure Gauge
	Warrenty	1year

## ELESTAR CATALOGUE

Product Table:

Dia. Size	1.5(40mm),2.0(50mm),2.5(63mm),3(75mm),4(100mm),6(150mm)
Dial Material	Aluminum
Case	Black steel
Bezel	Chromed plated
Window	Plastic or Glass
Thread	1/8,1/4, 3/8,1/2;PT(BSPT,ZG),BSP(G,PF),NPT etc.
Bourdon tube:	Copper alloy or Stainless steel 100Bar: C-Type ≥100Bar: Helical Type
Connection	Brass
Movement:	Brass
Range	-1Bar(-30Hg)-0-1000Bar(15000Psi)
Accuracy	±1%,±1.6%
Mounting type	bottom
Filled	Dry



047



FUJIAN ELESTAR MOTOR CO., LTD.

Liquid Fluid Water Level  
Controller Sensor Fs-2  
Cable Float Switch

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	300+	US \$1.80-10.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Export Standard Box

Product Attribute:	Principle	Cable
	Wires	PNP (Three-Wires)
	Contact Capacity	AC250V/10(4)a
	Output Signal	Spdt
	Working Temperature	0~60
	Working Pressure	More or Less0.5MPa
	Protection Grade	IP68
	Float Material	PP
	Float Size	79*103mm

## ELESTAR CATALOGUE

Product Table:

Product Name	Electrical pp plastic ball water float type level switch for air humidifier,coffee machine
Rated Voltage	AC 125-250V
Max.Current	AC 10(4)A
Frequency	50/60Hz
Max.Using Temperature	60
Protection Degree	IP68
Working Pressure	±0.5MPa
Float Material	PP
Float Size	79*103mm
Cable Material	PVC/Rubber
Cable Length	1m,2m,3m,4m,5m;Customized
Conductor Size	3*0.5mm <sup>2</sup> , 3*1.0mm <sup>2</sup>

048

Pressure Switch for Water Pump (PS-9)



Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	2,000-4,999	US \$2.40
	5,000-9,999	US \$2.20
	10,000-19,999	US \$2.10
	20,000+	US \$2.00

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Export Standard Box

Product Attribute:	Type	Mechanical
	Usage	Control Switch
	Application	Home, Commercial
	Explosion-Proof Type	Non Explosion-Proof
	Contact	Normally Close
	Certification	ISO9001, Ce
	Rated Voltage	110V/230V/380V
	Connector Size	Z1/4", G1/4", G3/8"
	Pressure Setting	1.4-2.8bar 2.1-3.5bar 1.4-4.2bar
	Protect Grade	IP44

## ELESTAR CATALOGUE

Product Table:

Descriptions:	
Rated Voltage:	110V/230V/380V
Max Current:	12A/6A
Pressure Range:	0.8-5.0bar
Pressure setting:	1.4-2.8bar 2.1-3.5bar 1.4-4.2bar
Joint Screw:	Z1/4
Protection Grade:	IP20
Working temperature:	0-55 degree
Application:	Self-Priming Pump/Jet Pump/Garden Pump/Clarified water Pump

049

Pressure Switch for Auto Pump (PS-3B)



FUJIAN ELESTAR MOTOR CO., LTD.

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	2,000-4,999	US \$1.50
	5,000-9,999	US \$1.40
	10,000-19,999	US \$1.30
	20,000-49,999	US \$1.25
	50,000+	US \$1.20

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Export Standard Box

Product Attribute:	Structure	Power Built-in Type
	Usage	Control Switch
	Application	Home, Industrial

Product Table:	Descriptions:	Pressure switch
	Rated Voltage:	110V/230V
	Max Current:	12A/6A
	Pressure Range:	0.8-3.5bar
	Pressure setting:	0.8-1.6bar 1.0-1.7bar 1.1-1.8bar 1.5-2.2bar
	Joint Screw:	ZG1/4
	Protection Grade:	IP20
	Working temperature:	0-55 degree
	Application:	Self-Priming Pump/Jet Pump/Garden Pump/Clarified water Pump

050



Ce Approved Pressure Switch for Water Pump (SK-6)

Contact Supplier

Price:	Min. Order(Pieces)	FOB Price
	2,000-4,999	US \$1.60
	5,000-9,999	US \$1.52
	10,000-19,999	US \$1.48
	20,000-49,999	US \$1.46
	50,000+	US \$1.42

Port: Fuzhou

Payment: L/C, T/T, D/P, Western Union, Paypal, Money Gram

Package: Export Standard Box

Product Attribute:		
Type		Mechanical
Usage		Control Switch
Application		Home, Commercial
Explosion-Proof Type		Non Explosion-Proof
Contact		Normally Close
Certification		ISO9001, Ce
Color		Grey/Black/Transparent
Screw		1/4" Male/Female

## ELESTAR CATALOGUE

Product Table:

Descriptions:	Pressure switch
Rated Voltage:	110V/230V
Max Current:	12A/6A
Pressure Range:	0.8-5.0bar
Pressure setting:	1.4-2.8bar 2.1-3.5bar 1.4-4.2bar
Joint Screw:	Z1/4
Protection Grade:	IP20
Working temperature:	0-55 degree
Application:	Self-Priming Pump/Jet Pump/Garden Pump/Clarified water Pump
Features:	According to the pressure changes in the pipe, it can open and close the pumps automatically